

SINOBASE™ Chemistry for the Water based Industry

BK3333 流平剂

产品描述:

西谱森 BK3333 流平剂是提升涂层表面质量的高效助剂，专为溶剂型、水性及 UV 固化涂料体系设计。它通过独特的聚醚改性聚二甲基硅氧烷结构，显著降低涂料的表面张力，提升底材润湿性和流平性，从而避免缩孔、鱼眼、橘皮等表面缺陷，使涂层获得更光滑、高光泽的外观。

产品特性:

外观	无色至浅棕色透明液体
化学成分	聚醚改性聚二甲基硅氧烷共聚体
有效成分	约 98%
pH 值	约 7

关键特性:

- * 优异的流平性：促进涂料均匀铺展，减少刷痕，提高表面平整度。
- * 强润湿能力：适用于低表面能基材（如塑料、金属、木材），防止润湿不良导致的缺陷。
- * 相溶性广泛：适用于溶剂型、无溶剂、水性及 UV 体系，不影响涂层间附着力。
- * 滑爽手感：赋予涂层细腻的触感，并提升抗划伤性
- * 抗粘连性（水性体系）：减少涂层在堆叠或卷材应用中的粘连风险。

包装和储存:

25KG/30kg/60kg 包装产品应贮存在（5-35℃）的密闭容器内，最好存放在阴凉干燥处，避免暴晒、冷冻及高温环境。



Toutes ces informations sont données à titre documentaire. Elles ne constituent en rien une spécification et ne garantissent ni l'utilisation ni la dépendance de brevets existants.
The information presented in this technical bulletin is given in good faith and is true and accurate to the best of our knowledge. No warranty or guarantee is expressed or implied regarding the accuracy of such data. It is the user's responsibility to determine the suitability for his own use of the information presented. No warranty or freedom is given regarding industrial property rights of sinobase or third parties.Document 1056, version 02, updated 09 August 2020.